Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/001065

International filing date: 22 March 2005 (22.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB

Number: 0406313.7

Filing date: 22 March 2004 (22.03.2004)

Date of receipt at the International Bureau: 09 May 2005 (09.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)










The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed


Dated 15 April 2005

Patents Form 1/77

Patents Act 1977 (Rule 16)

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road Newport South Wales NP10 800

1. Your reference

LAM/EMW/P/26154.GB

2. Patent application number (The Patent Office will fill in this part)

0406313.7

22 MAR 2004

 Full name, address and postcode of the or of each applicant (inderline all sumanes)

MR MUMTAZ SHAH, 96 Newport Road, Chorlton Cum Hardy, Manchester M21 9WN

Patents ADP number (if you know tt)

If the applicant is a corporate body, give the country/state of its incorporation

4372645002

4. Title of the invention

CUTTER APPARATUS

5. Name of your agent (afyou have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

WILSON GUNN M'CAW
5th Floor, Blackfriars House,
The Parsonage,
Manchester M3 2JA
UNITED KINGDOM

7153927001

Patents ADP number (If you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number (If you know it) Date of filing (day/month/year)

 If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application Number of earlier application

Date of filing (day/month/year)

 Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer Yes' 16)

ŇO

- e) any applicant named in part 3 is not an inventor, or
- there is an inventor who is not named as an applicant or
- c) any named applicant is a corporate body.
 See note (d))

009Parents Forth 1977

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

Claim (s)

Abstract

1 +1 Drawing (4)

10. If you are also filling any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

> Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Julyon boun M'hur Date Signature

22/03/2004

12. Name and daytime telephone number of person to contact in the United Kingdom

Ian A. Middlemist

0161 827 9400

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

10

15

20

25

1

CUTTER APPARATUS

This invention relates to a cutter apparatus for use in cutting sheet material such as paper, cloth or plastics such as PVC etc.

In WO 98/48981 I have disclosed apparatus for cutting sheet material which comprises a hand-manoeuvrable body comprising separate superimposed upper and lower parts with a gap between wherein sheet material can be received. The parts are physically connected only by a blade, or combination of blade and blade holders, and a pressure means in the form of a freely rotatable wheel is provided to tension the sheet in front of the blade. The gap may be sinusoidal, by forming the facing surfaces of the upper and lower parts with suitable contours for support and tensioning of the sheet, and a window or other viewing means is provided for viewing the sheet in front of the blade.

It has been found that the capabilities of this early model of sheet cutting apparatus are limited in some respects. Whilst cuts can be made to follow curved lines and in particular, the use of a wheel as a pressure means in front of the blade tends to limit the radius of curvature attainable and the minimum width of cut of material and impose a minimum radius of curvature for clean, snag-free cutting by the blade.

It is an object of the invention to provide a cutter apparatus for use in cutting sheet material such as paper cloth or plastics which has improved flexibility in use, for example attaining shorter radius curvature of clean snag-free cutting, and improved capabilities in other respects such as accuracy of tracking.

According to the invention, cutter apparatus comprises, an upper part and a lower part, a blade extending between the parts and forming the sole

10

15

20

25

connection between the parts and provided with a leading edge cutting edge, the upper part comprising a body adapted for manual manipulation, and the lower part providing opposed surfaces, a lower gliding surface and an upper paper guide surface for guiding paper between the parts and presenting the paper to the blade for cutting.

The apparatus preferably provides tensioning means in a zone around the blade, at least in front of and preferably to each side and extending behind the blade, in the form of protrusions on either the upper or lower parts of the apparatus. The protrusions are preferably provided one to each side of the blade and may be contoured to guide the paper by means of a curved lead-in surface. The pressure acting on the tensioning means may vary in response to changes in pressure exerted by a user on the upper part of the apparatus.

The lower part of the apparatus may be provided with notches or channels for cooperating with a rule or straight edge to guide the cutter apparatus for example for edge trimming.

A preferred embodiment of cutter apparatus according to the invention will now be described with reference to the accompanying drawings, wherein:-

Fig. 1 is a side elevation view of cutter apparatus according to the invention;

Fig. 2 is a front elevation of the apparatus shown in Fig. 1; and

Fig. 3 is a perspective view of the cutter apparatus of Figs. 1 and 2.

The cutter apparatus according to the invention shown in the drawings comprises an upper body 10, and a lower shoe 11 which are separated by a gap 12, and connected by a blade and holder combination 13 which has an upper end secured in the upper body 10 and a lower end

10

15

20

25

secured in the lower shoe 11. The upper body 10 comprises a plastics shell which is hollow but can be filled or partially filled, having a transparent window 14 or other viewing means in the front thereof, and the shell is shaped in a manner similar to an egg to be comfortably placed under the palm of a user's hand.

The blade/holder combination 13 features a cutting edge 15 at the leading edger of the blade.

The upper body 10 has a base part 16 which provides an upper guide surface bounding the gap 12, whilst the upper face of the shoe 11 provides a lower guide surface bounding the gap 12. The upper body may comprise a separately moulded cover part which is joined to the base part 16 to form the body 10.

The upper guide surface of the base part 16 is formed with tensioning means which takes the form of a protrusion 17, 18 to either side of and in front of the blade/holder combination 13, so that paper presented to the gap 12 to pass between the body 10 and shoe 11 is tensioned in the zone immediately in front of the cutting edge 15 as the cutter is pushed by hand to the right in Fig. 1, thereby bringing the paper under tension to the edge 15 and thus ensuring a clean cut. The protrusion can also be a part or more than one part placed around the blade, in front thereof and to each side and extending behind the latter.

The shoe 11 is formed with downwardly open notches 19, 20 to the front, one to each side of the centre line (or blade locus) of the cutter, which enable a rule or other straight edge to be inserted below the shoe 11, to guide the cutter as it is moved forward of a straight cut, for example in edge-trimming sheets, if required.

10

15

20


The cutter can also be used free-hand for making curved cuts, for example for use in cutting out to a pattern following pre-drawn lines. The window 14 helps with this as the precise alignment of the blade can be followed visually so that the path of the cutter can be manually adjusted by the user to follow a pre-drawn line.

The shoe 11 provides an under surface, either as a continuous under surface (save for the notches 19, 20) or as the lower edges of a peripheral skirt and is of general horse-shoe shape (best indicated in Fig. 3), although it can be of a semi-elliptical or oval shape or any other shape, which under surface provides a low resistance so that the shoe can be conveniently slid on a drawing board, desk or table surface below the paper, to move the cutter in response to control movements of the user manipulating the upper body 10.

The pressure exerted by the user may act to vary the tension exerted by the protrusions 17, 18 and the latter present a curved leading edge (see Fig. 1) for guiding the paper into the gap 12 towards the cutting blade edge 15 without snagging of the paper.

As the blade edge 15 is within the cutter with only a narrow gap between the parts 10, 11 and thus not accessible to fingers, the cutter is safe to use even for children.

It is of course to be understood that the invention is not intended to be restricted to the details of the above embodiments which are described by way of example only.



10

15

20

25

1

CUTTER APPARATUS

This invention relates to a cutter apparatus for use in cutting sheet material such as paper, cloth or plastics such as PVC etc.

In WO 98/48981 I have disclosed apparatus for cutting sheet material which comprises a hand-manoeuvrable body comprising separate superimposed upper and lower parts with a gap between wherein sheet material can be received. The parts are physically connected only by a blade, or combination of blade and blade holders, and a pressure means in the form of a freely rotatable wheel is provided to tension the sheet in front of the blade. The gap may be sinusoidal, by forming the facing surfaces of the upper and lower parts with suitable contours for support and tensioning of the sheet, and a window or other viewing means is provided for viewing the sheet in front of the blade.

It has been found that the capabilities of this early model of sheet cutting apparatus are limited in some respects. Whilst cuts can be made to follow curved lines and in particular, the use of a wheel as a pressure means in front of the blade tends to limit the radius of curvature attainable and the minimum width of cut of material and impose a minimum radius of curvature for clean, snag-free cutting by the blade.

It is an object of the invention to provide a cutter apparatus for use in cutting sheet material such as paper cloth or plastics which has improved flexibility in use, for example attaining shorter radius curvature of clean snag-free cutting, and improved capabilities in other respects such as accuracy of tracking.

According to the invention, cutter apparatus comprises, an upper part and a lower part, a blade extending between the parts and forming the sole

10

15

connection between the parts and provided with a leading edge cutting edge, the upper part comprising a body adapted for manual manipulation, and the lower part providing opposed surfaces, a lower gliding surface and an upper paper guide surface for guiding paper between the parts and presenting the paper to the blade for cutting.

The apparatus preferably provides tensioning means in a zone around the blade, at least in front of and preferably to each side and extending behind the blade, in the form of protrusions on either the upper or lower parts of the apparatus. The protrusions are preferably provided one to each side of the blade and may be contoured to guide the paper by means of a curved lead-in surface. The pressure acting on the tensioning means may vary in response to changes in pressure exerted by a user on the upper part of the apparatus.

The lower part of the apparatus may be provided with notches or channels for cooperating with a rule or straight edge to guide the cutter apparatus for example for edge trimming.

A preferred embodiment of cutter apparatus according to the invention will now be described with reference to the accompanying drawings, wherein:-

Fig. 1 is a side elevation view of cutter apparatus according to the invention;

Fig. 2 is a front elevation of the apparatus shown in Fig. 1; and Fig. 3 is a perspective view of the cutter apparatus of Figs. 1 and 2.

The cutter apparatus according to the invention shown in the

25 drawings comprises an upper body 10, and a lower shoe 11 which are

separated by a gap 12, and connected by a blade and holder combination 13

which has an upper end secured in the upper body 10 and a lower end

10

15

20

25

secured in the lower shoe 11. The upper body 10 comprises a plastics shell which is hollow but can be filled or partially filled, having a transparent window 14 or other viewing means in the front thereof, and the shell is shaped in a manner similar to an egg to be comfortably placed under the palm of a user's hand.

The blade/holder combination 13 features a cutting edge 15 at the leading edger of the blade.

The upper body 10 has a base part 16 which provides an upper guide surface bounding the gap 12, whilst the upper face of the shoe 11 provides a lower guide surface bounding the gap 12. The upper body may comprise a separately moulded cover part which is joined to the base part 16 to form the body 10.

The upper guide surface of the base part 16 is formed with tensioning means which takes the form of a protrusion 17, 18 to either side of and in front of the blade/holder combination 13, so that paper presented to the gap 12 to pass between the body 10 and shoe 11 is tensioned in the zone immediately in front of the cutting edge 15 as the cutter is pushed by hand to the right in Fig. 1, thereby bringing the paper under tension to the edge 15 and thus ensuring a clean cut. The protrusion can also be a part or more than one part placed around the blade, in front thereof and to each side and extending behind the latter.

The shoe 11 is formed with downwardly open notches 19, 20 to the front, one to each side of the centre line (or blade locus) of the cutter, which enable a rule or other straight edge to be inserted below the shoe 11, to guide the cutter as it is moved forward of a straight cut, for example in edge-trimming sheets, if required.

10

15

20

The cutter can also be used free-hand for making curved cuts, for example for use in cutting out to a pattern following pre-drawn lines. The window 14 helps with this as the precise alignment of the blade can be followed visually so that the path of the cutter can be manually adjusted by the user to follow a pre-drawn line.

The shoe 11 provides an under surface, either as a continuous under surface (save for the notches 19, 20) or as the lower edges of a peripheral skirt and is of general horse-shoe shape (best indicated in Fig. 3), although it can be of a semi-elliptical or oval shape or any other shape, which under surface provides a low resistance so that the shoe can be conveniently slid on a drawing board, desk or table surface below the paper, to move the cutter in response to control movements of the user manipulating the upper body 10.

The pressure exerted by the user may act to vary the tension exerted by the protrusions 17, 18 and the latter present a curved leading edge (see Fig. 1) for guiding the paper into the gap 12 towards the cutting blade edge 15 without snagging of the paper.

As the blade edge 15 is within the cutter with only a narrow gap between the parts 10, 11 and thus not accessible to fingers, the cutter is safe to use even for children.

It is of course to be understood that the invention is not intended to be restricted to the details of the above embodiments which are described by way of example only.